

# Technical Data Sheet



## nitrylex® pink

### PRODUCT DESCRIPTION

<b>Type of the glove</b>	Non-sterile, powder free, examination and protective glove for single use
<b>Material</b>	Nitrile
<b>Donning powder</b>	-
<b>Colour</b>	Pink
<b>Shape</b>	Ambidextrous, gloves fitting either hand
<b>Cuff</b>	Beaded
<b>External surface</b>	Microtextured + fingertip textured, polymerized
<b>Internal surface</b>	Polymerized + chlorinated
<b>Packaging</b>	10 x 100 pcs

### PRODUCT REFERENCES

SIZE / REFERENCE NUMBER	XS	RD30144001
	S	RD30144002
	M	RD30144003
	L	RD30144004
	XL	RD30144005

### PHYSICAL PROPERTIES

Dimensions	Size	XS	S	M	L	XL
		(5-6)	(6-7)	(7-8)	(8-9)	(9-10)
<b>Length [mm]</b>		240	240	240	240	240
<b>Width [mm]</b>		≤80	80	95	110	≥110
			±10	±10	±10	
<b>Thickness (single wall) [mm]</b>						
	Middle finger			0,05		
	Palm			0,05		
	Cuff			0,04		
<b>Elongation at break [%]</b>						
	Before ageing			500		
	After ageing			400		
	Minimum					
<b>Force at break [N]</b>						
	Before ageing			6,0		
	After ageing			6,0		
	Minimum					

### MANUFACTURING AND SAFETY STANDARDS

<b>AQL</b>	Manufacturing final release: G-I inspection level AQL 1.5 in accordance with ISO 2859-1	
<b>Protein content</b>	N/A	
<b>CE classification</b>	Class I – Medical Device (Council Directive 93/42/EEC)	Category III – Personal Protective Equipment (Council Directive 89/686/EEC)
<b>Compliances</b>	EN 455-1, EN 455-2, EN 455-3, EN 455-4 EN 980 EN 1041 EN ISO 13485	EN 374-1 (excluding clause 5.3.2), EN 374-2, EN 374-3 EN 420 EN 388
<b>Viral test</b>	Test in accordance with ASTM F1671	
<b>Cytostatics permeation</b>	N/A	
<b>Chemical substances permeation</b>	Test in accordance with EN 374-3	
<b>Food contact</b>	Declaration of conformity for food contact in accordance with Regulation (EC) No 1935/2004 and with Commission Regulation (EU) No 10/2011 and Overall Migration Test in accordance with Commission Regulation (EU) No 10/2011	
<b>Shelf life</b>	3 years	

### STORAGE

<b>Storage instruction</b>	Keep out of direct sunlight. Store in a cool, dry place in temperature 5-35° C. Keep away from sources of ozone and ignition.
	<b>Issue date:</b> 27.11.2017
	<b>Update:</b> 14.12.2017
	<b>Prepared by:</b> Wojciech Hercka – Technical Documentation Specialist
	<b>Approved by:</b> Iwona Miąsik – Products Group Manager